



単位mm

呼び径 (mm)	D	D1	Dr	Dr1	t	H	H1	Mコード
16X 13	29.0	24.0	29.0	24.0	3.5	41	38	11068
20X 13	33.0	24.0	33.0	24.0	3.5	46	40	11069
20X 16	33.0	29.0	33.0	29.0	3.5	48	45	11070
25X 13	40.0	24.0	40.0	24.0	4.0	51	43	11071
25X 16	40.0	29.0	40.0	29.0	4.0	53	48	11072
25X 20	40.0	33.0	40.0	33.0	4.0	55	53	11073
30X 13	46.0	24.0	46.0	24.0	4.0	55	46	11074
30X 16	46.0	29.0	46.0	29.0	4.0	57	51	11075
30X 20	46.0	33.0	46.0	33.0	4.0	59	56	11076
30X 25	46.0	40.0	46.0	40.0	4.0	62	61	11077
40X 13	57.0	24.0	57.0	24.0	4.5	66	52	11078
40X 16	57.0	29.0	57.0	29.0	4.5	68	57	11079
40X 20	57.0	33.0	57.0	33.0	4.5	70	62	11081
40X 25	57.0	40.0	57.0	40.0	4.5	73	67	11082
40X 30	57.0	46.0	57.0	46.0	4.5	76	71	11083
50X 13	70.0	24.0	70.0	24.0	5.0	74	58	11084
50X 16	70.0	29.0	70.0	29.0	5.0	76	63	11085
50X 20	70.0	33.0	70.0	33.0	5.0	78	68	11086
50X 25	70.0	40.0	70.0	40.0	5.0	81	73	11087
50X 30	70.0	46.0	70.0	46.0	5.0	84	77	11088
50X 40	70.0	57.0	70.0	57.0	5.0	90	88	11089
65X 40	87.0	57.0	88.5	57.0	6.6	100	95	11090
65X 50	87.0	70.0	88.5	70.0	6.6	101	104	11091
75X 25	102.0	40.0	104.5	40.0	8.0	93	88	11092
75X 40	102.0	57.0	104.5	57.0	8.0	100	102	11093
75X 50	102.0	70.0	104.5	70.0	8.0	105	110	11094
100X 50	130.0	70.0	133.5	70.0	10.0	125	122	11095
100X 75	130.0	102.0	133.5	104.5	10.0	140	132	11096
● 150X 75	186.0	102.0	190.0	104.5	13.0	208	158	11097
● 150X100	186.0	130.0	190.0	133.5	13.0	208	182	11098

- 備考 1. 水道用硬質ポリ塩化ビニル管継手 (JIS K 6743) による。
 2. Hの許容差は ± 1 mm、Rは10mm以上とする。
 3. D、Dr、D1、D'1、許容差のプラス側は、制限しない。
 4. ●印は、(株)クボタ製品です。

品名	HITS継手 異径チーゾ	型式 (略号)	HITT
	前澤化成工業株式会社	図番	01031350